



Premier


Ribbed Exhibit and Display Fabric



296 Nebula
PMS 2767C



R04 Monarch
PMS 281C / 282C



R05 Pacific
PMS 280C



R06 Indigo
PMS 294U




R09 Kelley Green
PMS 3425C




R07 Sand
PMS 467U




R08 Merlot
PMS 195C



R11 Electric Red
PMS 187C



R02 Steel
PMS 429U / 430U



R03 Charcoal
PMS 424C / 425C



R15 Cinder
PMS 426U



R01 Lava
PMS BLACK 6C 2X

*FLAMMABILITY: Premier and Regal have been tested against local and international standards and have received the following results:

- Meets Class A flame spread rating in accordance with ASTM E-84 "Tunnel Test"
- Passes corner burn- NFPA 265, UBC 8-2 (formerly UBC 42-2)(fully lined protocol)
- CAN/ULC-S102-M88 *Flammability test certificates available upon request.




Regal

Smooth Exhibit and Display Fabric



R02 Steel Chrome
PMS 429U / 430U



R03 Storm
PMS 424C / 425C



R11 Chili Pepper
PMS 187C



R04 Sapphire
PMS 281C / 282C



R01 Carbon
PMS BLACK 6C 2X



R05 Electric Blue
PMS 296



- Non-woven fabric will not fray or unravel
- Thermally activated synthetic fiber blend
- Uniform appearance with no linear pattern
- Cuts easily to any shape or size
- Resists stains, mold, and mildew
- Anti-static; resists lint, dust, and dirt
- Durable, dent-resistant, and easy to clean
- Velcro compatible; a hook monofilament of 7 to 8 mils (or less) is recommended
- Quality Systems ISO9001:2000 Laboratory Testing ISO17025
- Can be made with EcoSpun® (recycled fiber)
- Can be made with Fosshield® (antimicrobial fiber)
- Available in 63" wide rolls
- Custom colors and roll sizes available as well as pressure-sensitive backing